

AUTOGRADE MASKING TAPE

Autograde Masking Tape is a high-performance, no residue masking tape specifically made for automotive and general use. From auto grade applications to the exciting realm of car wrapping, this masking tape bridges the gap between precision and protection. Elevate your automotive projects with masking tape that delivers clean lines, prevents overspray, and safeguards surfaces.

CONSTRUCTION

ADHESIVE	RUBBER-BASED
LINER	YELLOW CREPE PAPER

TECHNICAL SPECIFICATIONS (TYPICAL VALUES)

THICKNESS	0.12MM
ADHESIVE STRENGTH	8N/25MM
HOLDING POWER	>2 HOURS
TEMPERATURE RANGE – SHORT TERM	120°C
TEMPERATURE RANGE – LONG TERM	-40°C TO 100°C

SURFACE PREPARATIONS AND FINISHING

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease and oil. Expected level of performance will be reached after a bonding period of 24 hours. Always test adhesion prior to application.

STORAGE AND SHELF LIFE

The shelf life of the tape is one year when stored at 18-25°C at 30-70% relative humidity and out of direct sunlight, in good packaging.

WARRANTY AND GUARANTEE

Rite Adhesives warrants that its' product complies, within its shelf life, to the specifications mentioned in this Technical Data Sheet.