


ET7-104 0.72W 3LED Module CW

CE ROHS IP67

ET7-104 : 0.72W

ABS shell, PC light lens, 1,0 mm MCPCB, Pure copper lines and 3LEDs 5050SMD.
Module Lens big beam angle: 160°

The most you can wire in a run is 40pcs of modules. The thickness of power wire should according to actual possible maximum current, the power of products, wiring length (suggest not exceeding 6M) and low voltage transmission line voltage drop. In measuring power use, the

Photometric Characteristics							
Model	Color	LED Qty	LM/1LED	(Nm/K) CCT (K)	LED type	Size (mm)	Prefab
Nil	Red	3	10 – 13	619 – 635	SMD5050	W15.71 *L66.5 *H7.7	20PCS/STING
	Green	3	10 -13	512 – 528			
	Blue	3	10 – 15	463 – 475			
	Yellow	3	10 – 15	463 - 475			
ET7-104	White	3	22 - 24	6500 - 9000			

Module Parameters:

Item	Parameters	Units
Working Voltage	12	VDC
Working Temperature	-35 ~ 55	°C
IP Grade	IP67	*
Dimensions	L40*W10*H10	Mm
Light Source Lifespan	≥50000	Hrs
Beam Angle	≥160°	*
Weight	0.0083	Kg

MTX5050-3-CW

CE ROHS