



A EUROTECH GROUP BRAND

EASY INSTALL SWIFT GLOSS

Item no. ET6-8000

Product Information

The EasyInstall Swift is an affordable temporary 100-micron white gloss, greyback calendared vinyl, with integrated bubble-free (air-egress) technology, that is ideal for short-term indoor and short-term outdoor signage, POS advertising and window decoration.

Shelf Life

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours after printing.

Technical Data

Carrier	Monomeric white gloss PVC self-adhesive vinyl
Thickness	100 μ (+/- 5%)
Adhesive	Grey removeable solvent-based acrylic
Adhesion	8 N/cm
Liner	Double-sided bubble-free PE coated kraft paper (140 g/m ²)
Application temperature	+10 up to +40°C
Temperature durability	-30 up to +80°C
Durability	Up to 2 years

Standard Dimensions

1370mm (wide) x 50m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.

Eurotech Australia
72 John Street
Welshpool 6106 WA

☎ 1800 30 61 61
✉ info@eurotech.com.au
🌐 eurotech.com.au

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every stage a test should be conducted on the original material.