

GAFFER SINGLE-SIDED CLOTH TAPE

Our Gaffer Tape is waterproof, leaves no residue behind and has exceptional tensile strength. It is commonly used to secure cables to a stage floor, podium, or another surface, either for safety or concealment. It is also frequently used for any impromptu fix, such as temporarily attaching fixtures or props or salvaging a broken piece of production equipment.

CONSTRUCTION

ADHESIVE	NATURAL RUBBER
CARRIER	N/A
LINER	COPOLYMER-COATED CLOTH

TECHNICAL SPECIFICATIONS (TYPICAL VALUES)

THICKNESS	0.3MM
ADHESIVE STRENGTH	25N/25MM
TENSILE STRENGTH	25KG/25MM
HOLDING POWER	>200 HOURS
APPLICATION TEMPERATURE MIN.	10°C
TEMPERATURE RANGE – SHORT TERM	80°C
TEMPERATURE RANGE – LONG TERM	-10°C TO 60°C

SURFACE PREPARATIONS AND FINISHING

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease and oil. Expected level of performance will be reached after a bonding period of 24 hours. Always test adhesion prior to application.

STORAGE AND SHELF LIFE

The shelf life of the tape is 18 months when stored at 18-25°C at 30-70% relative humidity and out of direct sunlight, in good packaging.

WARRANTY AND GUARANTEE

Rite Adhesives warrants that its' product complies, within its shelf life, to the specifications mentioned in this Technical Data Sheet.