



# BANNER UPS® BY BUDNICK PTAPE CLEAR

## Clear PowerTape® Hem Reinforcement Tape

Super strong Clear PowerTape® eliminates the need to fold & hem banner edges. It helps reduce edge curl and creates super-strong banners of almost any length in just a few easy steps. This single sided tape is typically used in conjunction with Banner Ups Clear PowerTabs® or BravoTabs®. Clear PowerTape® is great for two sided banner prints. Just apply over tabs along the top and bottom edges, then punch hole. Ropes are fastened to holes punched through the tape, tab, and banner media to maximize the tensile strength of the banner.

No folding required. Create a banner in only 3 minutes vs. 15-20 minutes with the old two sided tape and grommet method!

Clear PowerTape® is a high strength, engineered polymer film with high performance, high tack modified acrylic adhesive. Not recommended in contact with aliphatic or aromatic hydrocarbons. Banner Ups® & PowerTape® are registered trademarks of Budnick Converting.

Backing/Carrier		Tensile		Min. Application Temp	40° F
Adhesive		Elongation		Min. Service Temp	
Thickness		Adhesive Activation	Pressure	Max Short-Term Temp	
		Adhesion (unwind)		Max Long-Term Temp	

### PRODUCT FEATURES

- Faster, stronger & easier than grommets & sewing
- PowerTape® reduces edge curling
- Super strong engineered polymer backing
- High performance, high tack modified acrylic adhesive
- System creates stronger banners than typical grommets
- Power Tape eliminates the need for folding & sewing hems
- Resistant to water, detergent, & alcohol

### MARKETS SERVED

- Signage, Banners, & Printing

### ADHESIVE TAPE APPLICATIONS

- Banner hem reinforcement
- Alternative to folding & sewing banner hems

The physical properties listed are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must carry out their own tests to determine the suitability of the product for their internal use. Information is given in good faith, but without warranty.

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil.

Shelf life from date of manufacture is based on the product being stored at 70°F(21°C) / 50% relative humidity out of direct sunlight.

Specification compliance is dynamic and should only be used as a general guide. Always confirm that the tape you are interested in currently complies with all specification requirements. Please verify that the product number that you select is available in the proper size and color to meet your specification.