



A EUROTECH GROUP BRAND

GLOSS EASY INSTALL

Item no. **EV-ECO-GEI**



PVC FREE

Product Information

This glossy vinyl is a polypropylene film coated with a white gloss finish. It has a thickness of 60 microns and is **free from PVC**.

The film features a grey permanent adhesive for secure bonding. To facilitate easy installations, it is protected by a PE-coated air release liner weighing 135gsm.

This vinyl is well-suited for a variety of applications, both indoors and outdoors, including graphics, point-of-sale displays, exhibitions, and smooth surfaces.

It delivers vibrant and high-quality color prints with a glossy appearance. Moreover, it exhibits excellent dimensional stability, ensuring long-lasting results. For optimal outcomes, it is recommended to use this vinyl with Latex and UV printers.

Shelf Life

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Recommendations

Mounting to PVC substrates can cause the adhesive to transfer residue.

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

Technical Data

| | |
|-------------------------|---|
| Carrier | White gloss polypropylene (PP) |
| Total Thickness | 260 μ (+/- 5%) |
| Adhesive | Permanent grey acrylic |
| Adhesion | 17N/25mm |
| Liner | Air release PE coated paper (170 μ m) |
| Application temperature | +10 up to +40°C |
| Temperature durability | -30 up to +80°C |
| Outdoor durability | 5 years |

Standard Dimensions

1370mm (wide) x 50m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.

Eurotech Australia
72 John Street
Welshpool 6106 WA

☎ 1800 30 61 61
✉ info@eurotech.com.au
🌐 eurotech.com.au

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.