



A EUROTECH GROUP BRAND

FABRIX

Item no. EV-FAB-DIS

Product Information

Introducing Fabrix, the ultimate choice for crafting top-tier displays, including roll-ups, backdrops, pop-ups, frames, and exhibition displays.

Made from 100% polyester, Fabrix is engineered for superior durability, ensuring your displays maintain their quality over time. Weighing 315 ± 15 gsm with a thickness of 350 ± 40 µm, this fabric provides complete coverage, resulting in a captivating and professional display.

With an opacity of over 99%, Fabrix is the ideal choice for blackout applications, ensuring your visuals stand out without any interference.

Shelf Life

1 year when stored in the original packaging between 10°C and 30°C at 65% relative humidity.

Technical Data

Face	Matt Polyester (PET)
Backing	Grey PET
Thickness	350 µm (±5%)
Application temperature	+10 up to +40°C
Temperature durability	-20 up to +70°C
Ink compatibility	Solvent, Eco, Latex and UV

Standard Dimensions

914mm (wide) x 50m (long)
1524mm (wide) x 50m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.

Eurotech Australia
72 John Street
Welshpool 6106 WA

☎ 1800 30 61 61
✉ info@eurotech.com.au
🌐 eurotech.com.au

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every sale a test should be conducted on the original