

CAUTION PRINTED SURFACE PROTECTION TAPE

Our Surface Protection Tape, designed as a polyethylene film, serves as an effective solution for safeguarding surfaces in various applications. After application, the film forms a strong adherence to solid surfaces, yet it can be easily removed without leaving any residue behind. It acts as a protective barrier, shielding surfaces from scratches, abrasions, and other potential markings they may be vulnerable to, specifically during transportation.

CONSTRUCTION

ADHESIVE BASE	ACRYLIC
CARRIER	POLYETHYLENE

TECHNICAL SPECIFICATIONS (TYPICAL VALUES)

ELONGATION	300 - 400%
TENSILE STRENGTH	0.7 - 0.8KG/10MM
HEAT RESISTANCE	70 +/- 3°C for up to 48 hours
COLD RESISTANCE	-13 +/- 3°C for up to 48 hours
THICKNESS	40 - 150 MICRONS
WEATHERABILITY	200HR
PEEL ADHESION	350G/25MM

SURFACE PREPARATIONS AND FINISHING

Application temperature +10°C to +30°C (environment and substrate). Surfaces must be dry, clean and solid. Clean surfaces with an adequate cleaner.

SHELF LIFE

Store between +10°C and +30°C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging, and up to 6 months when stored outdoors (depending on multiple factors, like temperature, humidity, direct sun light, etc.).

WARRANTY AND GUARANTEE

Rite Adhesives warrants that its' product complies, within its shelf life, to its specifications.