

EVOLVE

A EUROTECH GROUP BRAND

VENTURE LAMINATE

Item no. EV6-8062

Product Information

The Venture Laminant is a premium 80-micron polymeric cold lamination film with a clear matt finish. Designed for use with Venture SAV and other self-adhesive vinyls, it offers excellent UV protection, strong adhesive performance, and up to 5 years of outdoor durability.

Available in 1370 mm x 50 m rolls, it is ideal for flat surface applications. Store between 20°C and 25°C with 50% to 55% relative humidity to maintain product integrity.

Shelf Life

12 months when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Technical Data

Carrier	Clear matt polymeric calendered PVC
Thickness	80µ (+/- 5%)
Adhesive	Clear solvent acrylic, permanent (25µ)
Adhesion	12 N/2.5cm
Liner	Two-sided PE coated kraft paper (145 g/m ²)
Application temperature	+10 up to +40°C
Temperature durability	-40 up to +80°C
Outdoor durability	5 years (unprinted film)

Standard Dimensions

1370mm (wide) x 50m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.

Eurotech Australia
72 John Street
Welshpool 6106 WA

1800 30 61 61
info@eurotech.com.au
eurotech.com.au

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.